Safety System Products

M12-M12-C-C813-G PUR

M12-CAN-connecting cable, 8 pin, 1 m



Your advantages

To the downloads ▶

we simplify safety

Safety System Products

M12-M12-C-C813-G PUR

8 pol. CAN Cable 1m, Connecting line HOLDX R_2

General data

Type designation	M12-M12-C-C813-G PUR
Item number	SP-X-33-000-56
Wiring color K1	WH,BN,GN,YW,GY,PK,BU,RD
Master HOLDX R2	□

Safety data

Approvals	UL2464

Environmental conditions

Max. operating temperature	-15 ... +55 °C

Electrical data

Pin assignment according DIN 47100	
1	White
2	Brown
3	Green
4	Yellow
5	Gray
6	Pink
7	Blue
8	Red

Mechanical data

Threaded ring material X1	H59 Kupfer
Housing material X1	PA
Threaded ring material X2	H59 copper
Shape of the plug connectors X2	M12 8-pin female connector
Housing material X2	PA
Housing colour X2	Black
Cable length L1	1000 mm

Safety System Products

M12-M12-C-C813-G PUR

Cable sheath material K1	PUR
Colour of cable outer sheathK1	Black
Conductor cross-section K1	0,25 mm²
Conductor material K1	Tinned copper
Conductor ínsulation K1	SR-PVC
Drag chain capability K1	No
Cable diameter K1	ø6,5 mm
Conductor cross-section AWG K1	22AWG

Electrical drawings

Pin assignment 1



Downloads

- Product line
- EPLAN-Data

we simplify safety