



SSP

Safety System Products

ATM-610A4-A

Process interlock, normally open (PTL), two connections

Your advantages

To the downloads ►



we simplify safety

ATM-610A4-A

General data

Item number	ITM-00278691
Functional type	Process interlock, normally open (PTL), two connections
Type designation	ATM-610A4-A

Safety data

Diagnostic coverage DC	Maximum 99% with appropriate monitoring
PFHd (EN ISO 13849)	4,16 x 10 ⁻⁹
Construction type (acc. to ISO 14119)	Type 4
Demand rate (acc. to IEC 62061)	High
Type of coding (according to EN ISO 14119)	High
Standards	ISO 14119, EN ISO 13849, IEC 61508, EN 60947-5-2, BS EN 62061
Category (EN ISO 13849-1:2015)	up to Category 4
SIL (acc. IEC 62061)	up to SIL3 CL3

Environmental conditions

operating environment	Indoor
Contamination level	2
Max. operating temperature	-20°C bis +55°C (-4°F bis +131°F) °C
Relative humidity	50% at 70°C
Altitude	2.000 m
Vibration resistance	Tested according to GS-ET-19 and EN 60947-5-2

Electrical data

Rated operating voltage U _e	24V DC (+10%, -15%) V
Rated insulation voltage U _i	60 V
Rated impulse withstand voltage U _{imp}	0,5 kV
Voltage drop U _d	< 3,5 V
Rated current (on 24 VDC)	400 mA
Current consumption	min. 100 mA



Safety System Products

ATM-610A4-A

Power consumption when switched off	< 0,5 mA
Rated conditional short-circuit	100 A
Overvoltage category	Type 2
Electromagnetic Compatibility (EMC)	Complies with EN 60947-5-3
Compliance with UL requirements	The unit must be operated on an energy-limited circuit. The power supply requires a 4 A fuse.
Design / Connections	1 x M12 8-pin male connector
Function type safety outputs	2 x OSSD

pin assignment with SSP accessories cable

1	Brown - UB
2	White - Safety input 1
3	Blue - 0 V
4	Black - Safety output 2
5	Grey

Response times

Safe response time	< 200 ms
Safe input "low" to safe output "low"	< 25 ms
Guard locking unlocked until safe output "low"	< 200 ms

Safety functions

Safety function 1	Secure inputs on
Safety function 2	Protective device closed
Safety function 3	Safety guard kept closed
Safe state 1	1 OSSD output off
Safe state 2	Protective device closed

Pin assignment connector 2 with SSP accessory cable

1	Brown
2	White
3	Blue - 0 V
4	Black - Solenoid On (guard locking locked)
5	Grey

Mechanical data


Housing material	Passivated and painted zinc alloy to BSEN12844 ZA3 and stainless steel acc. to BS3146-2:1975 (ANC4B)
------------------	--

ATM-610A4-A

Mechanical service life	1.000.000 switching cycles
Locking force Fmax	8.000 N
Locking force FZh	9.200 N
Maximum locking force F1max	12000 N
Minimally actuation radius	150 mm (see figure 5)
Maximum actuation frequency	720 switching cycles per hour

Electrical drawings


Pin assignment 1



ATM-610A4-A

Drawings

Dimensions



Equipment

Safety switches

SP-R-13-501-50



Mounting set for sliding doors 1 x angle fitting

ATM-KB

ITM-00335522



ATM-610A4-A

Mounting set for hinged doors 2 x angle fitting	ATM-KC	ITM-00344138	
Mounting set for hinged doors with handle	ATM-KH	ITM-00344139	
Mounting set for sliding doors with handle	ATM-KL	ITM-00335530	
Mounting set for sliding bolt with return spring without escape release	ATM-KS	ITM-00332039	
Accessories			
M12-female connector, 8 pin, 10 m	C8D10	SP-R-13-309-81	
M12-female connector, 8 pin, 25 m	C8D25	SP-R-13-309-67	
M12-female connector, 8 pin, 40 m	C8D40	SP-R-13-309-66	
M12-female connector, 8 pin, 5 m	C8D5	SP-R-13-309-80	
M12-connecting cable, 5 pin, 0,5 m	M12-M12-C5023-G	SP-X-33-000-10	

ATM-610A4-A

M12-connecting cable, 5 pin, 1 m	M12-M12-C513-G	SP-X-33-000-11	
Safe control technology			
Standard safety relay 1 safety function	S2 series	SP-K-70-001-00	
Time delay safety relay 1 safety function	T2 series	SP-K-70-001-02	
Multi-function safety relay 2 safety functions	X2 series	SP-K-70-001-03	

Downloads

- CAD Data
- Certificate UL
- Certificate TUV
- CAD Data