



EN4T6SL471N2UBWYNPF05 - Right Hand

Your advantages

- PLe according to EN ISO 13849-1
- Modular safety switch that adapts to your application
- Extracted key solution for lockout-tagout (LOTO) procedures
- Robust design

To the downloads ►







EN4T6SL471N2UBWYNPF05 - Right Hand

amGard pro is a modular and robust locking system. It is particularly suitable for heavy duty applications and can be easily adapted to the requirements of the customer thanks to its modular design. The configuration options are almost limitless and range from control modules and emergency locking through to emergency stop buttons and indicator lights.

Type designationEN4T6SL471N2UBWYNPF05 - Right HandItem numberITM - 00134615Safety dataCategory (EN ISO 13849-1:2015)cat. 4Environmental conditionsMax. operating temperature-5 + 50 °CElectrical dataB10d-value5.000.000Supply voltageDC +/- 10% 24 VMechanical dataLocking force Fmax10000 NActuating forceEN4 Unit: 2 NMHousing materialBSEN12844, stainless steel according to BS3146, unit: zinc alloy according to BS11004A	General data	
Safety data Category (EN ISO 13849-1:2015) cat. 4 Category (EN ISO 13849-1:2015) cat. 4 Cat. 4 Category (EN ISO 13849-1:2015) cat. 4 Cat. 4	Type designation	EN4T6SL471N2UBWYNPF05 - Right Hand
Category (EN ISO 13849-1:2015)cat. 4Environmental conditionsMax. operating temperature-5 + 50 °CBlod-value-5 + 50 °CSupply voltage5.000.000DC +/- 10% 24 VMechanical dataKechanical dataActuating force Fmax1000 NActuating forceEN4 Unit: 2 NMHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:	ltem number	ITM - 00134615
Environmental conditions Max. operating temperature -5 + 50 °C Electrical data B10d-value 5.000.000 Supply voltage DC +/- 10% 24 V Mechanical data Unit: 2 NM Actuating force Fmax 10000 N Actuating force EN4 Unit: 2 NM Housing material BSEN12844, stainless steel according to BS3146, unit:	Safety data	
Max. operating temperature-5 + 50 °CElectrical data-5 + 50 °CB10d-value5.000.000Supply voltageDC +/- 10% 24 VMechanical data-5 + 10% 24 VLocking force Fmax10000 NActuating forceEN4 Unit: 2 NMHousing materialHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:	Category (EN ISO 13849-1:2015)	cat. 4
Max. operating temperature-5 + 50 °CElectrical data-5 + 50 °CB10d-value5.000.000Supply voltageDC +/- 10% 24 VMechanical data-5 + 10% 24 VLocking force Fmax10000 NActuating forceEN4 Unit: 2 NMHousing materialHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:		
Flectrical data B10d-value 5.000.000 Supply voltage DC +/- 10% 24 V Mechanical data V Locking force Fmax 10000 N Actuating force EN4 Unit: 2 NM Housing material Head - EN4 and handle - T6: zinc alloy according to BSS1146, unit:	Environmental conditions	
B10d-value 5.000.000 Supply voltage DC +/- 10% 24 V Mechanical data Locking force Fmax 1000 N Actuating force Maxembox 1000 N Head - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:	Max. operating temperature	-5 + 50 °C
B10d-value 5.000.000 Supply voltage DC +/- 10% 24 V Mechanical data Locking force Fmax 1000 N Actuating force Maxembox 1000 N Head - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:		
Supply voltageDC +/- 10% 24 VMechanical data1000 NLocking force Fmax1000 NActuating forceEN4 Unit: 2 NMHousing materialHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:	Electrical data	
Mechanical dataLocking force Fmax10000 NActuating forceEN4 Unit: 2 NMHousing materialHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:	B10d-value	5.000.000
Locking force Fmax1000 NActuating forceEN4 Unit: 2 NMHousing materialHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:	Supply voltage	DC +/- 10% 24 V
Locking force Fmax1000 NActuating forceEN4 Unit: 2 NMHousing materialHead - EN4 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, unit:		
Actuating forceEN4 Unit: 2 NMHead - EN4 and handle - T6: zinc alloy according toHousing materialBSEN12844, stainless steel according to BS3146, unit:	Mechanical data	
Head - EN4 and handle - T6: zinc alloy according toHousing materialBSEN12844, stainless steel according to BS3146, unit:	Locking force Fmax	10000 N
Housing material BSEN12844, stainless steel according to BS3146, unit:	Actuating force	EN4 Unit: 2 NM
-		Head - EN4 and handle - T6: zinc alloy according to
zinc alloy according to BS1004A	Housing material	BSEN12844, stainless steel according to BS3146, unit:
		zinc alloy according to BS1004A

Downloads	
• Product line	

