



SSP

Safety System Products

EN2T6SL471N2B0WYNPF15 - Left Hand

Your advantages

- PLe according to EN ISO 13849-1
- Modular safety switch that adapts to your application
- Extracted key solution for lockout-tagout (LOTO) procedures
- Robust design

To the downloads ►



we simplify safety

EN2T6SL471N2B0WYNPF15 - Left Hand

amGard pro ist ein modulares und robustes Verriegelungssystem. Es eignet sich besonders für schwere Anwendungen und kann, dank seiner modularen Bauweise, spielend einfach an die Anforderungen des Kunden angepasst werden. Die Konfigurationsmöglichkeiten sind fast grenzenlos und reichen vom Steuermodul über Notentriegelung und Not-Aus-Schalter bis hin zur Meldeleuchte.

General data

Type designation	EN2T6SL471N2B0WYNPF15 - Left Hand
Functional type	Profisafe magnetic door locking with escape release (load current principle, electrical locking)
Item number	ITM - 00158746

Safety data

Category (EN ISO 13849-1:2015)	cat. 4
--------------------------------	--------

Environmental conditions

Max. operating temperature	-5 ... + 50 °C
----------------------------	----------------

Electrical data

B10d-value	5.000.000
Supply voltage	24V DC +/- 10% V

Mechanical data

Locking force Fmax	10000 N
Actuating force	EN2 unit: 2 NM
Housing material	Head - EN2 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, PROFIsafe unit: zinc alloy according to BS1004A

EN2T6SL471N2B0WYNPF15 - Left Hand

Downloads

- Product line