



SSP

Safety System Products

EN2T6SL411N2BUWYNPF05 - Left Hand

Your advantages

- PLe according to EN ISO 13849-1
- Modular safety switch that adapts to your application
- Extracted key solution for lockout-tagout (LOTO) procedures
- Robust design



To the downloads ►

we simplify safety

EN2T6SL411N2BUWYNPF05 - Left Hand

amGard pro is a modular and robust locking system. It is particularly suitable for heavy duty applications and can be easily adapted to the requirements of the customer thanks to its modular design. The configuration options are almost limitless and range from control modules and emergency locking through to emergency stop buttons and indicator lights.

General data

Type designation	EN2T6SL411N2BUWYNPF05 - Left Hand
Functional type	Profisafe magnetic door locking (closed current principle, mechanical locking)
Item number	ITM - 00134603

Safety data

Category (EN ISO 13849-1:2015)	cat. 4
--------------------------------	--------

Environmental conditions

Max. operating temperature	-5°C ... + 50°C °C
----------------------------	--------------------

Electrical data

B10d-value	5.000.000
Supply voltage	DC +/- 10% 24 V

Mechanical data

Locking force Fmax	10000 N
Actuating force	EN2 unit: 2 NM
Housing material	Head - EN2 and handle - T6: zinc alloy according to BSEN12844, stainless steel according to BS3146, PROFIsafe unit: zinc alloy according to BS1004A

EN2T6SL411N2BUWYNPF05 - Left Hand

Downloads

- Product line