



SSP

Safety System Products

EI4A6SR471N2UBWYNPF05 - Right Hand

Your advantages

- PLe according to EN ISO 13849-1
- Modular safety switch that adapts to your application
- Extracted key solution for lockout-tagout (LOTO) procedures
- Robust design



To the downloads ►

we simplify safety

EI4A6SR471N2UBWYNPF05 - Right Hand

amGard pro ist ein modulares und robustes Verriegelungssystem. Es eignet sich besonders für schwere Anwendungen und kann, dank seiner modularen Bauweise, spielend einfach an die Anforderungen des Kunden angepasst werden. Die Konfigurationsmöglichkeiten sind fast grenzenlos und reichen vom Steuermodul über Notentriegelung und Not-Aus-Schalter bis hin zur Meldeleuchte.

General data

Type designation	EI4A6SR471N2UBWYNPF05 - Right Hand
Functional type	Profisafe magnetic door locking with escape release (load current principle, electrical locking)
Item number	ITM - 00134622

Safety data

Category (EN ISO 13849-1:2015)	cat. 4
--------------------------------	--------

Environmental conditions

Max. operating temperature	-5 ... + 50 °C
----------------------------	----------------

Electrical data

B10d-value	5.000.000
Supply voltage	DC +/- 10% 24 V

Mechanical data

Locking force Fmax	10000 N
Actuating force	5 NM
Housing material	Handle - EI4A6: zinc alloy according to BSEN12844, stainless steel according to BS3146, PROFIsafe unit: zinc alloy according to BS1004A

EI4A6SR471N2UBWYNPF05 - Right Hand

Downloads

- Product line