



SSP

Safety System Products

EI4A6SR471N2B0WYNPF15 - Right Hand

Your advantages

- PLe according to EN ISO 13849-1
- Modular safety switch that adapts to your application
- Extracted key solution for lockout-tagout (LOTO) procedures
- Robust design



To the downloads ►

we simplify safety

EI4A6SR471N2B0WYNPF15 - Right Hand

amGard pro is a modular and robust locking system. It is particularly suitable for heavy duty applications and can be easily adapted to the requirements of the customer thanks to its modular design. The configuration options are almost limitless and range from control modules and emergency locking through to emergency stop buttons and indicator lights.

General data

Type designation	EI4A6SR471N2B0WYNPF15 - Right Hand
Functional type	Profisafe magnetic door locking with escape release (load current principle, electrical locking)
Item number	ITM - 00158744

Safety data

Category (EN ISO 13849-1:2015)	cat. 4
--------------------------------	--------

Environmental conditions

Max. operating temperature	-5 ... + 50 °C
----------------------------	----------------

Electrical data

B10d-value	5.000.000
Supply voltage	DC +/- 10% 24 V

Mechanical data

Locking force Fmax	10000 N
Actuating force	5 NM
Housing material	Handle - EI4A6: zinc alloy according to BSEN12844, stainless steel according to BS3146, PROFIsafe unit: zinc alloy according to BS1004A

EI4A6SR471N2B0WYNPF15 - Right Hand

Downloads

- Product line