



SSP

Safety System Products

SAFEGATE MZ L2XP TRX

Muting angle set with 2 MTRX (transceiver) sensors, L-logic (output only), crossed or parallel beams

Your advantages

To the downloads ►



we simplify safety

SAFEGATE MZ L2XP TRX

General data

Item number	SP-R-13-908-15
Type designation	SAFEGATE MZ T4P V
Functional type	Muting angle set with 2 MTRX (transceiver) sensors, L-logic (output only), crossed or parallel beams
Muting logic	L (one way) logic with 2 sensors - Crossed or parallel beams
Muting sensor field	Adjustable height and horizontal and vertical tilting
Characteristic output of the muting sensors	PNP 100 mA at 24 VDC
Muting sensors	Brackets for 2 single-beam retro-reflectors Muting sensors MTRX and 2 retro-reflectors
Integrated optoelectronic sensors	2 single-beam MTRX with crossed or parallel beams
Detection	Access control

Safety data

Approvals	CE; UKCA
-----------	----------

Environmental conditions

Max. operating temperature	- 30 ... 55 °C
Protective covers	None

Mechanical data

Max. Range (m)	45049
Mounting	Back slot, side slot with set of LL type brackets (included). SFB SG swivel brackets (optional)
Packaging dimensions HxLxW (mm)	145 x 450 x 200
Gross weight (g)	2107.8

SAFEGATE MZ L2XP TRX

Downloads

- SAFEGATE MZ L2XP TRX