



SSP

Safety System Products

EOS2 1353 X WTHF

**Safety light curtain with heated, waterproof housing,
IP69K/Ecolab certified, Automatic/Manual restart and EDM,
Pre-wired with 10 m lead cable**

Your advantages

[To the downloads ►](#)



we simplify safety



Safety System Products

EOS2 1353 X WTHF

General data

Type designation	EOS2 1353 X WTHF
Item number	SP-R-11-202-48
Functional type	Safety light curtain with heated, waterproof housing, IP69K/Ecolab certified, Automatic/Manual restart and EDM, Pre-wired with 10 m lead cable
Number of beams	68
Signalling	LEDs for status and diagnostics of the light curtain
Detection	Hand

Safety data

MTTFd (ISO 13849-1) years	100
SIL (acc. IEC 62061)	Typ 2 - SIL 1 - SILCL 1 - PL c - Cat. 2
PFHd (EN ISO 13849)	7.09E-08
Approvals	CE; TÜV SUD; UL Listed ESPE; TS - Taiwan; WEEE, insulation class low voltage; China RoHs; IP65 - IP67; IP69K; UKCA
Performance Level (EN ISO 13849-1: 2015)	Typ 2 - PL c
Safety functions	Integrated

Environmental conditions

Max. operating temperature	- 25 ... 50 °C
Protective covers	Food industry IP69K
Max. Water pressure (bar)	80 ... 100
Special versions	Waterproof housing Food and beverage Heated

Electrical data

Response times	17.5
Max. voltage (VDC)	24 ± 20%
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)

EOS2 1353 X WTHF

Mechanical data

Protected height (mm)	1360
Resolution (mm)	30
Controlled height (mm)	1350
Max. Range (m)	10
Restart	Built-in - user selectable automatic or manual
Total height (mm)	1537
Mounting	Set of 4 ring holders (included in delivery)
Max. Length of connection cable (m)	100
Connections	Cable output
Diameter (mm)	56
Packaging dimensions HxLxW (mm)	145 x 1660 x 200
Gross weight (g)	7592.49
Food-grade materials	Yes

Downloads

- EOS2 1353 X WTHF