



SSP

Safety System Products

M12-C81-G

M12-connector, 8 pin

Your advantages

To the downloads ►



we simplify safety

M12-C81-G

Straight M12-female connector, 8-pin ,cable-screw connector

General data

| | |
|-------------------|----------------|
| Type designation | M12-C81-G |
| Item number | 1022424 |
| Item number (old) | SP-X-33-001-02 |
| Functional type | connector |
| Codierung | A-coded |

Suitable for

| | |
|-------------------|--------------------------|
| HOLDX R1 | <input type="checkbox"/> |
| Master HOLDX R2 | <input type="checkbox"/> |
| SAFIX 3 | <input type="checkbox"/> |
| ATOM | <input type="checkbox"/> |
| EOS4 X receiver | <input type="checkbox"/> |
| EDI B7B | <input type="checkbox"/> |
| EDI C7 | <input type="checkbox"/> |
| EDI E1 | <input type="checkbox"/> |
| Safety Simplifier | <input type="checkbox"/> |
| Simplifier XCONN | <input type="checkbox"/> |
| XCONN | <input type="checkbox"/> |

Safety data

| | |
|---------------|--------|
| Approvals | UL2464 |
| IP protection | IP67 |

Environmental conditions

| | |
|----------------------------|-----------|
| Max. operating temperature | -10~80 °C |
| Max. storage temperature | -10~80 °C |

Electrical data

| | |
|-----------|------|
| Shielding | none |
|-----------|------|

Mechanical data

| | |
|---------------|-----|
| Connection X1 | M12 |
|---------------|-----|



Safety System Products

M12-C81-G

| | |
|---------------------------|---------------------|
| Connector type X1 | female connector |
| Connecting direction X1 | straight |
| Threaded ring material X1 | Nickel-plated brass |
| Number of pins X1 | 8 |

Downloads

- Product line