



SSP

Safety System Products

EOS2 1653 XS2

Safety light curtain for hand detection for cascade switching with automatic/manual restart and EDM (second-tier slave model)

Your advantages

[To the downloads ►](#)



we simplify safety

EOS2 1653 XS2

General data

Item number	SP-R-13-202-78
Type designation	EOS2 1653 XS2
Functional type	Safety light curtain for hand detection for cascade switching with automatic/manual restart and EDM (second-tier slave model)
Master Slave Models	Yes
Number of beams	83
Signalling	LEDs for status and diagnostics of the light curtain
Detection	Hand

Safety data

SIL (acc. IEC 62061)	Typ 2 - SIL 1 - SILCL 1 - PL c - Cat. 2
MTTFd (ISO 13849-1) years	131.7
PFHd (EN ISO 13849)	8.37E-08
Approvals	CE; TÜV SUD; UL Listed ESPE; TS - Taiwan; WEEE, insulation class low voltage; China RoHs; IP65 - IP67; UKCA
Performance Level (EN ISO 13849-1: 2015)	Typ 2 - PL c
Safety functions	Integrated

Environmental conditions

Max. operating temperature	- 30 ... 55 °C
Protective covers	None

Electrical data

Response times	See technical manual
Max. voltage (VDC)	24 ± 20%
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)

Mechanical data

Protected height (mm)	1660
-----------------------	------

EOS2 1653 XS2

Resolution (mm)	30
Controlled height (mm)	1650
Max. Range (m)	12
Restart	Built-in - user selectable automatic or manual
Total height (mm)	1736.5
Cross-sectional dimensions (mm)	28 x 30
Mounting	Back slot with LE-type brackets (included in delivery) or at the top and bottom with SFB E swivel brackets (optional)
Max. Length of connection cable (m)	100 (50 between master and slave)
Connections	M12 5-pole connectors
Packaging dimensions HxLxW (mm)	0 x 0 x 0

Downloads

- EOS2 1653 XS2