



# SSP

Safety System Products

## EOS2 1804 XS2

**Safety light curtain for hand detection for cascade switching with automatic/manual restart and EDM (second-tier slave model)**

### Your advantages

[To the downloads ►](#)



**we simplify safety**

## EOS2 1804 XS2

### General data

|                     |                                                                                                                               |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Item number         | SP-R-13-203-79                                                                                                                |
| Type designation    | EOS2 1804 XS2                                                                                                                 |
| Functional type     | Safety light curtain for hand detection for cascade switching with automatic/manual restart and EDM (second-tier slave model) |
| Master Slave Models | Yes                                                                                                                           |
| Number of beams     | 61                                                                                                                            |
| Signalling          | LEDs for status and diagnostics of the light curtain                                                                          |
| Detection           | Hand                                                                                                                          |

### Safety data

|                                          |                                                                                                             |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| SIL (acc. IEC 62061)                     | Typ 2 - SIL 1 - SILCL 1 - PL c - Cat. 2                                                                     |
| MTTFd (ISO 13849-1) years                | 159                                                                                                         |
| PFHd (EN ISO 13849)                      | 6.88E-08                                                                                                    |
| Approvals                                | CE; TÜV SUD; UL Listed ESPE; TS - Taiwan; WEEE, insulation class low voltage; China RoHs; IP65 - IP67; UKCA |
| Performance Level (EN ISO 13849-1: 2015) | Typ 2 - PL c                                                                                                |
| Safety functions                         | Integrated                                                                                                  |

### Environmental conditions

|                            |                |
|----------------------------|----------------|
| Max. operating temperature | - 30 ... 55 °C |
| Protective covers          | None           |

### Electrical data

|                    |                                                                                                          |
|--------------------|----------------------------------------------------------------------------------------------------------|
| Response times     | See technical manual                                                                                     |
| Max. voltage (VDC) | 24 ± 20%                                                                                                 |
| Safety output type | 2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal |
| Safety outputs     | 2 OSSD PNP (400 mA at 24 VDC)                                                                            |

### Mechanical data

|                       |      |
|-----------------------|------|
| Protected height (mm) | 1810 |
|-----------------------|------|

## EOS2 1804 XS2

|                                     |                                                                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Resolution (mm)                     | 40                                                                                                                          |
| Controlled height (mm)              | 1800                                                                                                                        |
| Max. Range (m)                      | 12                                                                                                                          |
| Restart                             | Built-in - user selectable automatic or manual                                                                              |
| Total height (mm)                   | 1886.5                                                                                                                      |
| Cross-sectional dimensions (mm)     | 28 x 30                                                                                                                     |
| Mounting                            | Back slot with LE-type brackets (included in delivery)<br>or at the top and bottom with SFB E swivel brackets<br>(optional) |
| Max. Length of connection cable (m) | 100 (50 between master and slave)                                                                                           |
| Connections                         | M12 5-pole connectors                                                                                                       |
| Packaging dimensions HxLxW (mm)     | 0 x 0 x 0                                                                                                                   |

### Downloads

- EOS2 1804 XS2