



SSP

Safety System Products

C8D5

M12-female connector, 8 pin, 5 m

Your advantages

To the downloads ►



we simplify safety



Safety System Products

C8D5

M12-cable, 8-pins, 8 x 0,34 mm², open end, 5 m

General data

Type designation	C8D5
Wiring color K1	WH,BN,GN,YW,GY,PK,BU,RD
HOLDX R1	<input type="checkbox"/>
Master HOLDX R2	<input type="checkbox"/>
SAFIX 3	<input type="checkbox"/>
ATOM	<input type="checkbox"/>
EOS4 X receiver	<input type="checkbox"/>
EDI B7B	<input type="checkbox"/>
EDI C7	<input type="checkbox"/>
EDI E1B	<input type="checkbox"/>
Safety Simplifier	<input type="checkbox"/>
Simplifier wireless distributor	<input type="checkbox"/>
XCONN	<input type="checkbox"/>

Safety data

Approvals	UL2464
-----------	--------

Environmental conditions

Max. operating temperature	-15 ... +55 °C
----------------------------	----------------

Electrical data

Pin assignment according DIN 47100

1	White
2	Brown
3	Green
4	Yellow
5	Gray
6	Pink
7	Blue
8	Red

Mechanical data

Conductor cross-section K1	0,34 mm ²
----------------------------	----------------------

C8D5

Electrical drawings

Pin assignment 1



Drawings

Dimensions



Downloads

- Product line
- EPLAN-Data