



SSP

Safety System Products

EOS4 153 XH WTHF

Safety light curtain for hand detection with heated, waterproof housing, IP69K/Ecolab certified, Automatic/Manual restart and EDM, Pre-wired with 10 m line cable

Your advantages

[To the downloads ►](#)



we simplify safety



Safety System Products

EOS4 153 XH WTHF

General data

| | |
|------------------|---|
| Item number | SP-R-11-102-90 |
| Type designation | EOS4 153 XH WTHF |
| Functional type | Safety light curtain for hand detection with heated, waterproof housing, IP69K/Ecolab certified, Automatic/Manual restart and EDM, Pre-wired with 10 m line cable |
| Number of beams | 8 |
| Signalling | LEDs for status and diagnostics of the light curtain |
| Detection | Hand |

Safety data

| | |
|--|---|
| SIL (acc. IEC 62061) | Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4 |
| MTTFd (ISO 13849-1) years | 100 |
| PFHd (EN ISO 13849) | 9.13E-09 |
| Approvals | CE; TÜV SUD; UL Listed ESPE; S Mark - Korea; TS - Taiwan; WEEE; Insulation Class; Low Voltage; China RoHs; IP65 - IP67, IP69K, UKCA |
| Performance Level (EN ISO 13849-1: 2015) | Type 4 - PL e |
| Safety functions | Integrated |

Environmental conditions

| | |
|----------------------------|---|
| Protective covers | Food industry IP69K |
| Max. operating temperature | - 25 ... 50 °C |
| Max. Water pressure (bar) | 80 ... 100 |
| Special versions | Waterproof housing Food and beverage Heated |
| Protection class | IP69K |

Electrical data

| | |
|--------------------|--|
| Response times | 3 |
| Safety output type | 2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal |

EOS4 153 XH WTHF

| | |
|----------------|-------------------------------|
| Safety outputs | 2 OSSD PNP (400 mA at 24 VDC) |
|----------------|-------------------------------|

Mechanical data

| | |
|-------------------------------------|--|
| Resolution (mm) | 30 |
| Protected height (mm) | 160 |
| Controlled height (mm) | 150 |
| Max. Range (m) | 17 |
| Restart | Built-in - user selectable automatic or manual |
| Total height (mm) | 337 |
| Mounting | Set of 4 ring holders (included in delivery) |
| Max. Length of connection cable (m) | 100 |
| Connections | Cable output |
| Diameter (mm) | 56 |
| Packaging dimensions HxLxW (mm) | 145 x 460 x 200 |
| Gross weight (g) | 3337.49 |
| Food-grade materials | Yes |

Downloads