



# SSP

Safety System Products

## EOS4 2B XH WTHF

**Safety light curtain for access control with heated, waterproof housing, IP69K/Ecolab certified, Automatic/Manual restart and EDM, Pre-wired with 10 m line cable**

### Your advantages

[To the downloads ►](#)



**we simplify safety**

## EOS4 2B XH WTHF

### General data

Item number	SP-R-11-106-75
Type designation	EOS4 2B XH WTHF
Functional type	Safety light curtain for access control with heated, waterproof housing, IP69K/Ecolab certified, Automatic/Manual restart and EDM, Pre-wired with 10 m line cable
Number of beams	2
Signalling	LEDs for status and diagnostics of the light curtain
Detection	Access control

### Safety data

SIL (acc. IEC 62061)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
MTTFd (ISO 13849-1) years	100
PFHd (EN ISO 13849)	9.15E-09
Approvals	CE; TÜV SUD; UL Listed ESPE; TS - Taiwan; WEEE, insulation class low voltage; China RoHs; IP65 - IP67; IP69K; UKCA
Performance Level (EN ISO 13849-1: 2015)	Type 4 - PL e
Safety functions	Integrated

### Environmental conditions

Max. operating temperature	- 25 ... 50 °C
Protective covers	Food industry IP69K
Max. Water pressure (bar)	80 ... 100
Special versions	Waterproof housing   Food and beverage   Heated
Protection class	IP69K

### Electrical data

Response times	2.5
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal

## EOS4 2B XH WTHF

Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
----------------	-------------------------------

### Mechanical data

Protected height (mm)	510
Resolution (mm)	Multiple beams
Max. Range (m)	17
Restart	Built-in - user selectable automatic or manual
Total height (mm)	777
Mounting	Set of 4 ring holders (included in delivery)
Max. Length of connection cable (m)	100
Packaging dimensions HxLxW (mm)	145 x 900 x 200
Gross weight (g)	4822.89
Food-grade materials	Yes

### Downloads