



SSP

Safety System Products

EOS4 1501 XS2

Safety light curtain for finger detection for cascade switching with automatic/manual restart and EDM (second-tier slave model)

Your advantages

[To the downloads ►](#)



we simplify safety

EOS4 1501 XS2

General data

Item number	SP-R-13-100-49
Type designation	EOS4 1501 XS2
Functional type	Safety light curtain for finger detection for cascade switching with automatic/manual restart and EDM (second-tier slave model)
Master Slave Models	Yes
Number of beams	150
Signalling	LEDs for status and diagnostics of the light curtain
Detection	Finger

Safety data

MTTFd (ISO 13849-1) years	262.6
SIL (acc. IEC 62061)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
PFHd (EN ISO 13849)	2.31E-08
Approvals	CE; TÜV SUD; UL Listed ESPE; S Mark - Korea; TS - Taiwan; WEEE; Insulation Class; Low Voltage; China RoHs; IP65 - IP67; IP69K; UKCA
Performance Level (EN ISO 13849-1: 2015)	Type 4 - PL e
Safety functions	Integrated

Environmental conditions

Max. operating temperature	- 20 ... 55 °C
Protective covers	None
Protection class	IP65 - IP67

Electrical data

Response times	See technical manual
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)

Mechanical data

Resolution (mm)	14
-----------------	----

EOS4 1501 XS2

Protected height (mm)	1510
Controlled height (mm)	1500
Max. Range (m)	6
Restart	Built-in - user selectable automatic or manual
Total height (mm)	1586.5
Cross-sectional dimensions (mm)	28 x 30
Mounting	Rear slot with a set of LE brackets (included in the scope of delivery) or at the top and bottom with SFB E swivel brackets (optional)
Max. Length of connection cable (m)	100 (50 between master and slave)
Connections	M12 5-pin connectors
Packaging dimensions HxLxW (mm)	0 x 0 x 0
Gross weight (g)	0

Downloads

- EOS4 1501 XS2