



SSP

Safety System Products

EOS4 1803 A

Safety light curtain for hand detection with automatic restart

Your advantages

To the downloads ►



we simplify safety

EOS4 1803 A

General data

Item number	SP-R-13-102-71
Type designation	EOS4 1803 A
Functional type	Safety light curtain for hand detection with automatic restart
Number of beams	91
Signalling	LEDs for status and diagnostics of the light curtain
Detection	Hand

Safety data

SIL (acc. IEC 62061)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
MTTFd (ISO 13849-1) years	124.8
PFHd (EN ISO 13849)	2.15E-08
Approvals	CE; TÜV SUD; UL Listed ESPE; S Mark - Korea; TS - Taiwan; WEEE; Insulation Class; Low Voltage; China RoHs; IP65 - IP67; IP69K; UKCA
Performance Level (EN ISO 13849-1: 2015)	Type 4 - PL e
Safety functions	With external module

Environmental conditions

Max. operating temperature	- 30 ... 55 °C
Protective covers	None
Protection class	IP65 - IP67

Electrical data

Response times	22
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)

Mechanical data

Protected height (mm)	1810
-----------------------	------

EOS4 1803 A

Resolution (mm)	30
Controlled height (mm)	1800
Max. Range (m)	12
Restart	Automatic
Total height (mm)	1863
Cross-sectional dimensions (mm)	28 x 30
Mounting	Rear slot with a set of LE brackets (included in the scope of delivery) or at the top and bottom with SFB E swivel brackets (optional)
Max. Length of connection cable (m)	100
Connections	M12 5-pin connectors
Packaging dimensions HxLxW (mm)	145 x 1920 x 200
Gross weight (g)	5638.76

Equipment

Accessories

M12-female connector, 5 pin, 10 m	CD10	SP-R-13-309-56	
M12-female connector, 5 pin, 15 m	CD15	SP-R-13-309-52	
M12-female connector, 5 pin, 20 m	CD20	SP-R-13-309-57	
M12-female connector, 5 pin, 25 m	CD25	SP-R-13-309-49	

EOS4 1803 A

M12-female connector, 5 pin, 5 m

CD5

SP-R-13-309-50



M12-female connector, 5 pin, 50 m

CD50

SP-R-13-309-65



Downloads

- EOS4 1803 A