



SSP

Safety System Products

EOS4 1055 AH

**Safety light curtain for body detection with automatic restart,
Increased range**

Your advantages

To the downloads ►



we simplify safety

EOS4 1055 AH

General data

Item number	SP-R-13-104-56
Type designation	EOS4 1055 AH
Functional type	Safety light curtain for body detection with automatic restart, Increased range
Number of beams	28
Signalling	LEDs for status and diagnostics of the light curtain
Detection	Body

Safety data

MTTFd (ISO 13849-1) years	480.5
SIL (acc. IEC 62061)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
PFHd (EN ISO 13849)	1.24E-08
Approvals	CE; TÜV SUD; UL Listed ESPE; S Mark - Korea; TS - Taiwan; WEEE; Insulation Class; Low Voltage; China RoHs; IP65 - IP67; IP69K; UKCA
Performance Level (EN ISO 13849-1: 2015)	Type 4 - PL e
Safety functions	With external module

Environmental conditions

Max. operating temperature	- 20 ... 55 °C
Protective covers	None
Protection class	IP65 - IP67

Electrical data

Response times	5.5
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and polarity reversal
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)

Mechanical data

Resolution (mm)	50
-----------------	----

EOS4 1055 AH

Protected height (mm)	1060
Controlled height (mm)	1050
Max. Range (m)	20
Restart	Automatic
Total height (mm)	1113
Cross-sectional dimensions (mm)	28 x 30
Mounting	Rear slot with a set of LE brackets (included in the scope of delivery) or at the top and bottom with SFB E swivel brackets (optional)
Max. Length of connection cable (m)	100
Connections	M12 5-pin connectors
Packaging dimensions HxLxW (mm)	145 x 1170 x 200
Gross weight (g)	3600.26

Equipment

Accessories

M12-female connector, 5 pin, 10 m	CD10	SP-R-13-309-56	
M12-female connector, 5 pin, 15 m	CD15	SP-R-13-309-52	
M12-female connector, 5 pin, 20 m	CD20	SP-R-13-309-57	
M12-female connector, 5 pin, 25 m	CD25	SP-R-13-309-49	

EOS4 1055 AH

M12-female connector, 5 pin, 5 m

CD5

SP-R-13-309-50



M12-female connector, 5 pin, 50 m

CD50

SP-R-13-309-65



Downloads