



SSP

Safety System Products

EDI A5B

Illuminated emergency stop button with key release

Your advantages

- Robust design
- User-friendly status display via coloured marking of the emergency stop button
- Featuring jam protection collars
- User-friendly status display via coloured marking of the emergency stop button
- Manipulation detection through key unlocking
- Optional self-monitoring contactors can detect any faults (incorrect installation of the emergency stop button or a dropped contact block)



To the downloads ►

we simplify safety

EDI A5B

The EDI emergency stop buttons have a modular design.

Select the head, contact and if desired the corresponding housing or simply immediately select the EDI slimline variant in a slimline housing. The special feature of the EDI buttons is the optionally available self-monitoring contact.

To help maintain safety, the switching elements in the emergency stop buttons/emergency off buttons are fitted with a safety contact. This constantly monitors the proper connection between the emergency stop button/emergency off button and the contact element. Even redundant, secure emergency off chains are ineffective if the contact is not perfectly connected to the emergency off actuator. If the emergency stop button/emergency off button becomes disconnected from the contact element due to negligent installation or mechanical damage, the safety contact trips immediately and the machine is shut down. The machine can only be placed into operation again when the fault has been rectified.

General data

Item number	SP-G-60-000-10
Functional type	Illuminated emergency stop button with key release

Safety data

Approvals	TÜV_SÜD, CE
-----------	-------------

Environmental conditions

Max. storage temperature	-50 ... +85 °C
Max. operating temperature	-30 ... +55 °C

Electrical data

Illumination	24V / 15mA AC/DC
--------------	------------------

Mechanical data

Mounting position	any
Installation opening	22,3

EDI A5B


Torque (mounting nut)	max. 2,5 Nm
Mechanical service life	50.000 switching cycles

Equipment

Operating elements

Contact modules (direct opening mechanism)	EDI ZA1	SP-G-62-000-07	
Contact modules (direct opening mechanism)	EDI ZA2	SP-G-62-000-03	
Contact modules (direct opening mechanism)	EDI ZB1	SP-G-62-000-06	
Contact modules, self-monitoring	EDI ZB2	SP-G-62-000-02	
Contact modules, Quick-connect Terminal	EDI ZC1	SP-G-62-000-05	
Contact modules	EDI ZC2	SP-G-62-000-01	
Contact modules, Quick-connect Terminal for LED light	EDI ZD1	SP-G-62-000-08	

EDI A5B

Module connection element for LED light	EDI ZD2	SP-G-62-000-04	
Module attachment for 3 modules spring-loaded terminals	EDI ZH1	SP-G-62-000-11	
Module attachment for 3 modules screw terminals	EDI ZH2	SP-G-62-000-10	
Module holder for 5 modules screw terminals	EDI ZI2	SP-G-62-000-09	
Empty housing for EDI A	EDI ZK4	SP-G-62-000-14	
Empty housing for EDI A	EDI ZK5	SP-G-62-000-15	
Empty housing for EDI A	EDI ZK8	SP-G-62-000-16	

EDI A5B

Downloads

- CAD-Data
- Certificate
- Product line
- Operating manual
- Operating manual
- EPLAN-Data