



# SSP

---

Safety System Products

## SAFIX T6

### Flat actuator for SAFIX 3

#### Your advantages

- Flat actuator

[To the downloads](#) ►



**we simplify safety**



## Safety System Products

### SAFIX T6

The new SAFIX 3 RFID safety sensor impresses due to its compact design and a hole distance of 22 mm. It can be actuated from the front and both sides and is available in 3 different versions with a choice of low level or high level coding according to EN ISO 14119. The sensor has protection class IP69K, holds an ECOLAB approval and can either be purchased with an M12, 8-pin pigtail cable or a fixed cable length of 5 or 10 metres.

Thanks to its OSSD output signals, the sensor can be connected to all standard control and safety relays. A total of up to 30 sensors can be switched in series. An information signal and a three colour LED display on the sensor are provided for diagnosis purposes

#### General data

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Type designation                   | SAFIX T6                          |
| Item number                        | SP-E-76-000-61                    |
| Functional type                    | RFID safety sensor, flat actuator |
| Approvals                          | TÜV_SÜD, CE                       |
| Performance level (EN ISO 13849-1) | PLe                               |
| SIL                                | SIL3, SILCL3                      |
| Category (EN ISO 13849)            | Kat. 4                            |
| Service life TM (EN ISO 13849-1)   | 20 Years                          |

#### Mechanical data

##### Dimensions

|        |         |
|--------|---------|
| Width  | 13,4 mm |
| Length | 53,4 mm |

#### Downloads

- Operating manual
- Certificate
- SISTEMA - Data V 4.0
- CAD Data
- Product line
- Catalog