






Safety System Products

Selector switch G1

2 Positions, non-lathing, 1x NC + 1x NO, without labeling

Your advantages

To the downloads ▶



we simplify safety

Safety System Products

Selector switch G1

- Unlit
- non-latching
- Contact 1x NC + 1x NO
- without labeling

General data	
Item number	SP-X-88-000-23
Type designation	G1
Labelling	Without
Switching mode	non-latching
Installation opening button	Ø 0.88 in / Ø 22.3 mm

Safety data	
Approvals	CE

Electrical data	
Bounce time	<10 ms
Bounce time NC	<10 ms ms
mechanical lifespan	30.000 switching cycles
Rated operating voltage Ue	24 V
Rated operating current I	0.25 A
Switch type	Turnkey (NO) 1, Opener (NC) 1
Illumination	No
	<20 mOhm
Break contact force opening	According to EN60947-5-1, Appendix K
electrical lifespan	1.000.000 switching cycles
	<20 mOhm
Switching capacity	10 Ie
Continuous thermal current	5 A
Connecting typ	spring balancer clamp
Number of pins	6
Wire size	
Single - wire	28...20 AWG / 0.08...0.5 mm²

we simplify safety

Safety System Products

Selector switch G1

Fine - wire	28...20 AWG / 0.08...0.5 mm²
Fine - wire (wire end ferrule with plastic collar)	0.25 mm² / 24 AWG
Fine - wire (wire end ferrule without plastic collar)	0.25 mm² / 24 AWG
Wire stripping	5...6 mm / 0.2...0.24 in

Mechanical data


Torque (mounting nut)	1.5...1.9 Nm

Electrical drawings

Safety System Products

Selector switch G1

Connection example 1



Safety System Products

Selector switch G1

Downloads

- Touch Panel
- Product line