



SSP
Safety System Products

Illuminated selector switch G4

2 Positions, latching, 1 x NC + 1 x NO

Your advantages

To the downloads ►



we simplify safety

Illuminated selector switch G4

- Illuminated
- latching
- Contact 1 x NC + 1 x NO
- Without labeling

General data

Item number	SP-X-88-000-26
Type designation	Simplifier G4
Labelling	without
Number switch positions	2
Switching mode	latching
Installation opening button	Ø 0.88 in / Ø 22.3 mm

Safety data

Approvals	CE
-----------	----

Electrical data

Bounce time	<10
Bounce time NC	<10 ms
mechanical lifespan	1.000.000 switching cycles
Rated operating voltage U _e	24 V
Rated operating current I _∞	0.25 A
Switch type	Turnkey (NO) 1, Opener (NC) 1, LED 1
Illumination	LED
	<20 mOhm
Break contact force opening	According to EN60947-5-1, Appendix K
electrical lifespan	1.000.000 switching cycles
	<20 mOhm
Switching capacity	10 le
Continuous thermal current	5 A
Connecting typ	Spring balancer clamp
Number of pins	6

Wire size

Illuminated selector switch G4

Single - wire	28...20 AWG / 0.08...0.5 mm ²
Fine - wire	28...20 AWG / 0.08...0.5 mm ²
Fine - wire (wire end ferrule with plastic collar)	0.25 mm ² / 24 AWG
Fine - wire (wire end ferrule without plastic collar)	0.25 mm ² / 24 AWG
Wire stripping	5...6 mm / 0.2...0.24 in



Mechanical data

Torque (mounting nut)	1.5...1.9 Nm
-----------------------	--------------

Electrical drawings

Illuminated selector switch G4

Connection example 1

Artikelcode	Beleuchteter Wahlschalter 2 Positionen rastend G4
	 
SP-X-88-000-26	

Illuminated selector switch G4

Downloads

- Touch Panel
- Product line