





Safety System Products

Illuminated selector switch G12

3 Positions, non-latching, 2 x NO

Your advantages

To the downloads ▶



we simplify safety

Safety System Products

Illuminated selector switch G12

- Unlit
- non-latching
- Contact 2 x NO
- Individual labeling

General data	
Item number	SP-X-88-000-34
Type designation	Simplifier G12
Labelling	Individual
Number switch positions	2
Switching mode	non-latching
Installation opening button	Ø 0.88 in / Ø 22.3 mm

Safety data	
Approvals	CE

Electrical data	
Bounce time	<10
mechanical lifespan	1.000.000 switching cycles
Rated operating voltage Ue	24 V
Rated operating current I	0.25 A
Switch type	Turnkey (NO) 2
Illumination	LED
electrical lifespan	1.000.000 switching cycles
	<20 mOhm
Switching capacity	10 Ie
Continuous thermal current	5 A
Connecting typ	Spring balancer clamp
Number of pins	6
Wire size	
Single - wire	28...20 AWG / 0.08...0.5 mm²
Fine - wire	28...20 AWG / 0.08...0.5 mm²
Fine - wire (wire end ferrule with plastic collar)	0.25 mm² / 24 AWG

we simplify safety

Safety System Products

Illuminated selector switch G12

Fine - wire (wire end ferrule without plastic collar)	0.25 mm² / 24 AWG
Wire stripping	1.5...1.9 Nm

Mechanical data


Torque (mounting nut)	1.5...1.9 Nm

Electrical drawings

Safety System Products

Illuminated selector switch G12

Connection example 1



we simplify safety

Safety System Products

Illuminated selector switch G12

Downloads

- Touch Panel
- Product line