



SSP

Safety System Products

Illuminated selector switch G15

3 Positions, latching, 2 x NO

Your advantages

[To the downloads ►](#)



we simplify safety

Illuminated selector switch G15

- Unlit
- latching
- Contact 2 x NO
- Individual labeling

General data

Item number	SP-X-88-000-37
Type designation	Simplifier G15
Labelling	Individual
Number switch positions	3
Switching mode	latching
Installation opening button	Ø 0.88 in / Ø 22.3 mm

Safety data

Approvals	CE
-----------	----

Electrical data

Bounce time	<10
mechanical lifespan	1.000.000 switching cycles
Rated operating voltage U _e	24 V
Rated operating current I ₀	0.25 A
Switch type	Turnkey (NO) 2, LED 1
electrical lifespan	1.000.000 switching cycles
	<20 mOhm
Switching capacity	10 I _e
Continuous thermal current	5 A
Connecting typ	Spring balancer clamp
Number of pins	6

Wire size

Single - wire	28...20 AWG / 0.08...0.5 mm ²
Fine - wire	28...20 AWG / 0.08...0.5 mm ²
Fine - wire (wire end ferrule with plastic collar)	0.25 mm ² / 24 AWG
Fine - wire (wire end ferrule without plastic collar)	0.25 mm ² / 24 AWG

Illuminated selector switch G15

Wire stripping	5...6 mm / 0.2...0.24 in
----------------	--------------------------

Mechanical data

Torque (mounting nut)	1.5...1.9 Nm
-----------------------	--------------

Electrical drawings

Connection example 1

we simplify safety

Illuminated selector switch G15

Downloads

- Touch Panel
- Product line