



SSP


Safety System Products

Selector switch G17

2 Positions, non-latching, 1 x NC + 1 x NO

Your advantages

To the downloads ►



we simplify safety

Selector switch G17

- Unlit
- non-latching
- Contact 1 x NC + 1 x NO
- Individual labeling

General data

Item number	SP-X-88-000-39
Type designation	Simplifier G17
Labelling	Individual
Number switch positions	2
Switching mode	non-latching
Installation opening button	Ø 0.88 in / Ø 22.3 mm

Safety data

Approvals	CE
-----------	----

Electrical data

Bounce time	<10
mechanical lifespan	1.000.000 switching cycles
Rated operating voltage U _e	24 V
Rated operating current I _∞	0.25 A
Switch type	Turnkey (NO) 1, Opener (NC) 1
Illumination	No
	<20 mOhm
electrical lifespan	1.000.000 switching cycles
Switching capacity	10 I _e
Continuous thermal current	5 A
Connecting typ	Spring balancer clamp
Number of pins	6

Wire size

Single - wire	28...20 AWG / 0.08...0.5 mm ²
Fine - wire	28...20 AWG / 0.08...0.5 mm ²
Fine - wire (wire end ferrule with plastic collar)	0.25 mm ² / 24 AWG

Selector switch G17

Fine - wire (wire end ferrule without plastic collar)	0.25 mm ² / 24 AWG
Wire stripping	5...6 mm / 0.2...0.24 in



Mechanical data

Torque (mounting nut)	1.5...1.9 Nm
-----------------------	--------------

Electrical drawings

Selector switch G17

Connection example 1

Artikelcode	Wahlschalter 2 Positionen tastend Individuelle Beschriftung G17  
SP-X-88-000-39	

Selector switch G17

Downloads

- Touch Panel
- Product line