






SSP
Safety System Products

Keyswitch K3

2 Positions, non-latching, 2 x NO

Your advantages

To the downloads ▶



we simplify safety

Safety System Products

Keyswitch K3

- non-latching
- Contact 2 x NO
- Without labeling

General data	
Item number	SP-X-88-000-47
Type designation	Simplifier K3
Labelling	Without
Number switch positions	2
Switching mode	non-latching
Installation opening button	Ø 0.88 in / Ø 22.3 mm

Safety data	
Approvals	CE

Electrical data	
Bounce time	<10
mechanical lifespan	1.000.000 switching cycles
Rated operating current I	0.25 A
Switch type	Turnkey (NO) 2
Illumination	No
electrical lifespan	1.000.000 switching cycles
Switching capacity	10 Ie
Continuous thermal current	5 A
Connecting typ	Spring balancer clamp
Number of pins	6
Wire size	
Single - wire	28...20 AWG / 0.08...0.5 mm²
Fine - wire	28...20 AWG / 0.08...0.5 mm²
Fine - wire (wire end ferrule with plastic collar)	0.25 mm² / 24 AWG
Fine - wire (wire end ferrule without plastic collar)	0.25 mm² / 24 AWG
Wire stripping	5...6 mm / 0.2...0.24 in

we simplify safety

Safety System Products

Keyswitch K3

Mechanical data


Torque (mounting nut)	1.5...1.9 Nm

Electrical drawings

Safety System Products

Keyswitch K3

Connection example 1



Safety System Products

Keyswitch K3

Downloads

- Touch Panel
- Product line
- Operating Instructions