



Safety System Products

Project Basics

Date

Customer

Project/Commission

End customer

Drawing number customer

Contact

Name

Phone

E-mail

Range

☐ Safety fence ☐ Electrical components

☐ Measurement ☐ Final assembly

☐ Risk assessment ☐ Overrun measurement

Safety fence

Model safety fence

☐ Flex-Line ☐ Flex-Line pro

☐ Combi-Line ☐ Easy-Line

Protection height fence

☐ 2200 mm* ☐ 2000 mm

☐ 2400 mm ☐

Ground clearance

☐ ≤120 mm* ☐

Profile design

☐ anodized* ☐ nature

☐ coated according to RAL 1023 ☐ coated according to

Cover strips

☐ No cover strips*

☐ Cover strips
☐ Outside only
☐ Close all open grooves

☐ Cover strips plastic 40 mm traffic yellow, RAL 1023

☐ Cover strips anodized aluminum

☐ Cover strips plastic flush 11 mm

☐ Black, RAL 9005

☐ Traffic yellow, RAL 1023

☐ Light gray, RAL 7035

☐

*) Standard

we simplify safety



Safety System Products

Project Basics

Filling safety fence

- ☐ Spot weld mesh
 - ☐ 40x40, coated black RAL 9005*
 - ☐ 40x40, galvanized
 - ☐ 30x30, coated black RAL 9005
 - ☐ 30x30, galvanized
 - ☐ 20x80, coated black RAL 9005
 - ☐
- ☐ Polycarbonat
 - ☐ 5 mm transparent*
 - ☐ 5 mm transparent ESD-capable
 - ☐ 4 mm transparent
 - ☐ 6 mm transparent
 - ☐ 3 mm welding protection black/brown
 - ☐

- ☐ Sheet metal
 - ☐ Steel sheet 1.0 mm anodized cambered
 - ☐ Aluminum sheet 2 mm anodized
 - ☐ Perforated plate 1.5 mm Qg10-14 coated black RAL 9005
 - ☐

- ☐ Aluminum composite
 - ☐ 4 mm composite panel
- ☐ Glass
 - ☐ 5 mm single-pane safety glass (ESG)
 - ☐ 6 mm laminated safety glass (VSG)

Door accessories

- ☐ Adapter plates for door interlock
 - Door lock type
- ☐ Reach-through protection
- ☐ Double ball catch closer
- ☐ Door handle
- ☐ Door opening limitation
- ☐ Danger sign
- ☐

Quick extraction field

- ☐ With special key*
- ☐ With square key
- ☐ None

Special environmental conditions

- ☐

Floor mounting

- ☐ Floor angle aluminum*
- ☐ Floor angle steel galvanized
- ☐ Adjustable feet
- ☐

Ground anchoring

- ☐ Expansion anchor*
- ☐ Screw anchor
- ☐ Composite anchor
- ☐ None
- ☐

*) Standard



Safety System Products

Project Basics

Safety switch

☐ Performance Level according to DIN EN ISO 13849

☐ Not known

☐ PLc

☐ PLd

☐ PLe

Manipulation incentive according to DIN EN ISO 14119

☐ No (standard coded)

☐ Yes (high coded)

☐ Door stop

☐ Left

☐ Right

☐ Escape release

☐ Emergency stop

☐ Guard locking

☐ Control keys, quantity

☐ Voltageless open

☐ Voltageless closed
(overrun or falling loads)

Connection type

☐ Conventional

☐

☐ Bus-system

☐ Wireless Safety

☐ ASi-Bus

☐ PROFI-safe

☐ EtherNet/IP (Rockwell)

Light curtains

☐ Light curtains

☐ Length

☐ Resolution

☐ Muting

*) Standard

we simplify safety



Project Basics